

# TRADE MAX $\text{C}\epsilon$ PNEUMATIC TAPPING TOOL

## 手持氣動攻牙器

### Type ATH-12-1

手持氣動萬向攻牙器  
Pneumatic Various degree Tapping Hand Tool



### Type ATH-12-2

手持夾頭氣動攻牙器  
Pneumatic Chuck Tapping Hand Tool



### Type ATH-12-3

手持氣動扭力攻牙器  
Pneumatic Torsional Tapping Hand Tool




COCCHIOLA SA

4115-7007  
630\*3315

Model 型號	For Top 攻牙能力	Speed (rpm) 主軸轉速	Spindle Type	Max.Air Consumption (Nm <sup>3</sup> / min)	Air House Size (mm)	Weigth (kg) 重量	Parts 附件
ATH-12-1	M2~M12	250	HTP/B12	0.4	9.5	2.5	扳手
ATH-12-2	M2~M12	250	CAP10/B12	0.4	9.5	2.5	扳手
ATH-12-3	M2~M12	250	TH1/B12	0.4	9.5	4	六個扭力筒夾+扳手

## HYDRAULIC TAPPING MACHINE


### 油壓攻牙機




Model 型號	HMT-24	HM-24	HMT-32	HM-32	HMT-42	HM-42	HMT-50	HM-50
For Tap 攻牙能力	M3~M22		M4~M32		M4~M42		M4~M50	
Speed(rpm) 主軸轉速	0~400		0~550 / 0~150		0~400 / 0~75		0~360 / 0~60	
Work Range(mm) 工作範圍	Rmax 最大半徑	1600	1600	1600	1600	1600	1600	1600
	Rmin 最小半徑	200	200	200	200	200	200	200
Voltage 電壓	220/380V, 50/60Hz, 3-PHASE							
Electric Motor 馬力	3Hp		3Hp		3Hp		5Hp	
Hydraulic Pressure 油壓壓力	100 Kg/cm <sup>2</sup>		100 Kg/cm <sup>2</sup>		100 Kg/cm <sup>2</sup>		140 Kg/cm <sup>2</sup>	
Weight(kg) 重量	400/500	300/400	400/500	300/400	400/500	300/400	400/500	300/400




自動噴油攻牙裝置  
Automatic Tap  
Lubricator System  
TM 800030



眼鏡蛇噴油器  
Cobra  
Lubricator System  
TM 800031



立式與水平氣動鑽孔座  
Pneumatic Vertical and Horizontal  
Drilling / Tapping Device  
ADV-10 / ADVH-10



氣動攻牙機、裝置磁性座  
Portable & Moveable Magnetic Base  
TLM-300 夾持力: 300kg  
TLM-600 夾持力: 600kg

## ELECTRIC TAPPING MACHINE

### 電動攻牙器




Model 型號	EMT-32	
For Tap 攻牙能力	M3 ~ M32	
Speed (rpm) 主軸轉速	0~300 / 0~55	
Work Range 工作範圍	最大半徑 Rmax (mm)	1500
	最小半徑 Rmin (mm)	200
Voltage 電壓	220 V 2-PHASE	
Electric Motor 馬力	0.75 kw	
Weight (kg) 重量(淨/毛)	260	
Code 訂購編號	0136 10000332	

# TRADE MAX

# AIR TAPPING MACHINE

## 氣動攻牙機



Model 型號	AQ-08-950	AQ-12-950	AQ-16-1000	AQ-20-1000	AQ-22-1000	AQ-24-1000	AQ-27-1000
For Tap 攻牙能力	M2~M8	M3~M12	M3~M16	M3~M20	M3~M22	M3~M24	M3~M27
Speed(rpm) 主軸轉速	700	400	300	150/400	120/300	90/280	70/220
Work Range(mm) 工作範圍	Rmax 950 Rmin 100	Rmax 950 Rmin 100	Rmax 1000 Rmin 100	Rmax 1000 Rmin 100	Rmax 1000 Rmin 100	Rmax 1000 Rmin 100	Rmax 1000 Rmin 100
Weight(kg) 重量	16	16	24	25	25	25	25




Model 型號	AS-08 / II	AS-12 / II	AS-16 / II	AS-20 / II	AS-22 / II	AS-24 / II	AS-27 / II
For Tap 攻牙能力	M2~M8	M3~M12	M3~M16	M3~M20	M3~M22	M3~M24	M3~M27
Speed(rpm) 主軸轉速	700	400	300	150/400	120/300	90/280	70/220
Work Range(mm) 工作範圍	Rmax 1400 Rmin 200	Rmax 1400 Rmin 200	Rmax 1400 Rmin 200	Rmax 1400 Rmin 200	Rmax 1400 Rmin 200	Rmax 1400 Rmin 200	Rmax 1400 Rmin 200
Weight(kg) 重量	21	21	26	27	27	27	27



Model 型號	AT-08 / I	AT-12 / I	AT-16 / I	AT-20 / I	AT-22 / I	AT-24 / I	AT-27 / I
For Tap 攻牙能力	M2~M8	M3~M12	M3~M16	M3~M20	M3~M22	M3~M24	M3~M27
Speed(rpm) 主軸轉速	700	400	300	150/400	130/300	90/280	70/220
Work Range(mm) 工作範圍	Rmax 1600 Rmin 500	Rmax 1600 Rmin 500	Rmax 1600 Rmin 500	Rmax 1600 Rmin 500	Rmax 1600 Rmin 500	Rmax 1600 Rmin 500	Rmax 1600 Rmin 500
Weight(kg) 重量	20	20	25	36	36	36	36



Model 型號	AT-08 / II	AT-12 / II	AT-16 / II
For Tap 攻牙能力	M2~M8	M3~M12	M3~M16
Speed(rpm) 主軸轉速	700	400	300
Work Range(mm) 工作範圍	Rmax 1900 Rmin 200	Rmax 1900 Rmin 200	Rmax 1900 Rmin 200
Weight(kg) 重量	23	23	27



Model 型號	AT-20 / II	AT-22 / II	AT-24 / II	AT-27 / II
For Tap 攻牙能力	M3~M20	M3~M22	M3~M24	M3~M27
Speed(rpm) 主軸轉速	150/400	120/300	90/280	70/220
Work Range(mm) 工作範圍	Rmax 1900 Rmin 200	Rmax 1900 Rmin 200	Rmax 1900 Rmin 200	Rmax 1900 Rmin 200
Weight(kg) 重量	38	38	38	38


### 90° 或任意角度攻牙機配件 90° and Various Degree Tapping Device




AQ.AS.AT08/12



AQ.AS.AT08/12



AQ.AS.AT16/20/22/24/27



AQ.AS.AT16/20/22/24/27

Model 型號	W kg 重量
AQ.AS.AT08-90°	2
AQ.AS.AT12-90°	2
AQ.AS.AT16-90°	2
AQ.AS.AT20-90°	2
AQ.AS.AT22-90°	2
AQ.AS.AT24-90°	2
AQ.AS.AT27-90°	2

# TRADE MAX

MAHO ENTERPRISE CO.,LTD.