

**AMOLADORAS RECTAS / Straight Grinders / Esmerilhadeiras Retas**

MODELO	VELOCIDAD rpm	L x Ø mm	CONSUMO Ln/min	POTENCIA H.P.	CONEXION B.S.P.	MANG. " x mts.	PESO Kg.	CAPACIDAD PIEDRA	TIPO
Model	Speed	L x Ø	Air cons.	Power	Connection	Tube	Weight	Capac. stone	Type
Modelo	Rotações	L x Ø	Cons. de ar	Potência	Conex. ar	Mangueira	Peso	Cap. Rebolo	Tipo
AAN-22	22.000	150/36	220	0.50	1/4	1/4" X 5	0,90	1"	Pinza
AAN-22/45	22.000	270/44	220	0.50	1/4	1/4" X 5	1,00	1"	Pinza
AAN-22/90	22.000	270/44	220	0.50	1/4	1/4" x 5	1,00	1"	Pinza
AAN-25	20.000	178/40	260	0.50	1/4	3/8" X 5	0,90	1"1/2	Pinza
AAN-25AC	15.000	250/40	260	0.50	1/4	3/8" X 5	1,10	1"	Pinza
AAN-25AL	15.000	340/40	260	0.50	1/4	3/8" x 5	1,20	1"	Pinza
AAN-30	30.000	145/34	150	0.33	1/4	1/4" x 5	0,40	1"	Pinza
AAN-30L	30.000	245/34	150	0.33	1/4	1/4" x 5	0,60	1"	Pinza
AAN-50	16.000	320/55	340	0.75	1/4	3/8" x 5	1,50	2"	Pinza
AAN-50L	16.000	445/55	340	0.75	1/4	3/8" x 5	2,30	2"	Pinza
AAN-50T	16.000	450/55	340	0.75	1/2	3/8" x 5	1,70	2"	Pinza
AAN-50LT	16.000	570/55	340	0.75	1/2	3/8" x 5	2,50	2"	Pinza
AAN-70	70.000	140/29	170	0.33	1/4	1/4" x 5	0,40	1/4"	Pinza

MODELO	VELOCIDAD rpm	L x Ø mm	CONSUMO Ln/min	POTENCIA H.P.	CONEXION B.S.P.	MANG. " x mts.	PESO Kg.	CAPACIDAD PIEDRA	TIPO
Model	Speed	L x Ø	Air cons.	Power	Connection	Tube	Weight	Capac. stone	Type
Modelo	Rotações	L x Ø	Cons. de ar	Potência	Conex. ar	Mangueira	Peso	Cap. Rebolo	Tipo
AAN-50E	16.000	330/55	340	0.75	1/4	3/8" x 5	1.60	3"	Eje
AAN-50EL	16.000	455/55	340	0.75	1/4	3/8" x 5	2.30	3"	Eje
AAN-50ET	16.000	460/55	340	0.75	3/8	3/8" x 5	1.70	3"	Eje
AAN-50ELT	16.000	580/55	340	0.75	3/8	3/8" x 5	2.50	3"	Eje
AAN-100.6	6.000	475/65	350/400	2.00	3/8	1/2" x 5	4.00	4"	Eje
AAN-100.8	8.000	475/65	350/400	2.00	3/8	1/2" x 5	4.00	4"	Eje
AAN-150.4	4.500	500/70	400/500	3.00	3/8	1/2" x 5	4.50	6"	Eje
AAN-150.6	6.000	500/70	400/500	3.00	3/8	1/2" x 5	4.50	6"	Eje
AAN-200	8.000	500/80	450/550	4.00	3/8	1/2" x 5	5.00	6"	Eje